

Order- no.	Inner Ø mm / inch		Working pressure bar	Burst pressure bar	Bending radius ≈ mm
8006	6	1/4"	27	≥ 80	35
8008	8	5/16"	27	≥ 80	50
8010	10	3/8"	27	≥ 80	60
8013	13	1/2"	27	≥ 80	80
8016	16	5/8"	27	≥ 80	100
8019	19	3/4"	27	≥ 80	120
8025	25	1"	27	≥ 80	150



## Multi-Purpose Hose Type 80

The **@marsoflex**<sup>®</sup> Multi-Purpose Hose Type 80 is a multi-purpose discharge hose for many applications with high safety requirements.

This hose type is suitable for the discharge of air, water, oil, fats, petrol, nitrogen and miscellaneous chemicals.

The Type 80 hose is used in the chemical and mineral oil industry as well as in machine and plant manufacturing and mining.

Hose tube: NBR oil resistant, black, smooth Hose reinforcements: High-strength textile braids Hose cover: NBR, black, smooth. Resistant to oil, ozone and weather influences. Electrical resistance:  $R < 10^6 \Omega / m$ Temperature range: -25°C to +85°C (peak temperature up to 110°C) Roll length: 40 metres

(marsoflex\* Multi-Purpose Hoses Type 80 can be assembled, tested and marked with userspecific fittings and couplings. Corresponding certificates can be issued on request.

Technical specifications are subject to change without notice.

